

Notched flashing fixed to rib with
4.8mmØ aluminium rivets

Dimondek 400 clip fixed with 10g x
16mm wafer head tek screw

Dimondek® 400 wall cladding
(specify thickness and coating)

Roofing underlay and netting
shown dashed

130 mm min. medium wind speed areas or pitches greater than 10°.
200 mm min. high wind speed areas and higher or pitches less than 10°.

DHS girt

Line of structure

Notes:

- Foam closure strip only required if bird or vermin proofing is required, or if in a high wind area, there is a risk of windblown moisture entering the building.
- Leave foam out if ventilation is required.
- These details are suitably fixed to allow for a theoretical thermal movement of up to 10mm. For thermal movement greater than this a clipping system should be considered.

Dimondek 400 stop ended

Dimondek 400 stop ended

100mm min. lap

Dimondek 400 clip fixed with 10g x
45mm wafer head timbertite screw

Framing shown dashed for clarity

Dimond hi-span steel wall girt

Dimondek 400 clip fixed with 10g x
16mm wafer head tek screw

Dimondek® 400 wall cladding
(specify thickness and coating)

Building wrap shown dashed

Original Size A4



Dimondek 400

Roof

Roof - Wall Apex

File:	
Issue: 01	Reference
Scale: 1 : 5	dim_dd4_1060
Date: 28 November 2018	